




**OPGW Cable Specifications**

**TGG**

**Cable Type:** OPGW - 2S 1 / 24 ( M99 / R60 - 100 )

**Cross Section:**



**Fiber type:** 24xG.652D

<b>Design:</b>			
	Name	No	Material Dia.
Center	20%ACSwire	1	2.70 mm
Layer1	20%ACSwire	5	2.65 mm
	AA(LHA2)wire	0	
	SUS Tube	1 / 24	2.60 mm
Layer2	20%ACSwire	0	2.65 mm
	AA(LHA2)wire	12	

Stranded:core and layer1 greased	
stranding direction of outer layer is "right" hand(Z-stranding)	
Cable Diameter	13.30 mm
Cable Weight	424 kg/km

<b>Technical Data:</b>	according to: IEEE 1138 standards	
Supporting Cross Section		99.49 mm <sup>2</sup>
Section of ACS Wire / AA Wire	33.30 / 66.19 mm <sup>2</sup>	
Rate Tensile Strength (RTS)		59.7 kN
Modulus of Elasticity (E-Modulus)		97.5 kN/mm <sup>2</sup>
Thermal Elongation Coefficient		17.4 10 <sup>-6</sup> /°C
Permissible Maximum Working Stress(MAT) (40%RTS)		240.0 N/mm <sup>2</sup>
Everyday Stress (EDS) ( 16%~25%RTS)	96.0	~ 150.0 N/mm <sup>2</sup>
Strain Margin Stress (60%RTS)		360.0 N/mm <sup>2</sup>
DC Resistance ( 20 °C)		0.420 Ω / km
Short Circuit Current ( 1s, 20°C~200°C)		9.99 kA
Short Circuit Current Capacity ( 20°C~200°C ) (I <sup>2</sup> t)		99.78 kA <sup>2</sup> s
Minimum Bending Radius (installation)		≥ 333 mm
Installation Tensile Strength (≤20%RTS)		≤11.9 kN
<b>Temperature Range:</b>	Installation	-10°C ~ +50 °C
	Transportation and Operation	-40°C ~ +80 °C

Remarks: All Sizes and Values are Nominal Values

1 / 24 - Tubes / Fibers of Tube

M99 - Supporting Cross Section

R60 - Rate Tensile Strength (RTS)

100 - Short Circuit Current Capacity (20°C~200°C)

2018/8/7			OPGW	zjm_No:39N	Cathy
----------	--	--	------	------------	-------